



This Series of Hose Couplings are designed for use between the 3/4 inch diameter hose and pipe or other equipment with a male thread. The female thread size can be produced according to client's detailed requirement.

Technical Specifications:

Hose Ferrule: High-quality Brass with Electroplated Chrome Finish for Corrosion Resistance
Female Nut (female thread): High-quality Brass with Electroplated Chrome Finish for Corrosion Resistance
Inner Core Hose Shank: High-quality Brass
Design: Reinforced structure for improved strength and durability
Gasket in the female nut: Buna-N or Viton for option

Ordering Specifications:

Item No.	ID mm of hose	OD mm of hose	Female Thread
FGM-19-3/4LC	19 mm	28 mm	G3/4" BSPP
FGM-19-1LC	19 mm	28mm	G1" BSPP
FGM-19-3/4	19 mm	30 mm	G3/4" BSPP
FGM-19-1	19 mm	30 mm	G1" BSPP
FGM-19-30LPG	19 mm	31 mm	M30 X 1.5

NOTE: Since hose standards vary from country to country, hoses with the same inner diameter often have different outer diameters. The Hose Ferrule can be customized according to different outer diameters.

The assembler is responsible for the testing of the electrical conductivity of the hose line. After assembly of the hose tail, please check whether you can see the end of hose through the control opening.

Key Features:

High mechanical strength and longevity
Chrome-plated surface for excellent chemical and corrosion resistance
Easy assembly and disassembly
Secure connection with minimal pressure drop

More Photos of other sizes for reference:



For more information or custom requirements, please contact our technical support team or sales representative.