
Add:Bali Vallage Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

Reusable, self-closing Safety Swivel Break to EN 13617-2. Designed to protect dispenser, hose assembly and car against damage caused by drive-off incidents. Stops the flow of fuel on the hose end at separation. The 'Nozzle Break' is directly fitted into the nozzle.



HBLDF-8 Series of swivel breakaways are intended for easy installation at nozzle inlet. The compact, light weight design incorporate a 360 degree swivel rotation at both the male end and middle joint, with simple and easily re-connectable breakaway on the opposite end. The swivel breakaway will breakaway under a pull force of more than 350 lbs. Reconnection force is approximately 15 lbs.

Technical Specifications:

Inlet: BSPP or NPT 3/4" Female Thread
Outlet: 3/4"BSPP or NPT Male thread
Body Material: SS304
Gasket: Viton O-rings
Pull Force: 350 lbs.
Users: For AdBlue, Acid,Water etc.

Packing:

Carton Size: 27cm x 25cm x 27cm
Each Carton Quantity:50 Pcs/Carton
Each Carton Gross Weight:21Kg/Carton

Ordering Specifications:

<u>Item No.</u>	<u>Inlet Size and Thread Standard</u>	<u>Outlet Size and Thread Standard</u>
HBH-B-SS-3/4	BSPT, BSPP or NPT 3/4" Female	X BSPT, BSPP or NPT 3/4" Male