



Technical specifications:

Model: **HBLB19-3-15-220V**

Name: Electric Self-priming Diaphragm Pump

Flow range: 20 to 40 L/min

Nominal diameter: 3/4" BSPP Female (19 mm)

Motor: 370W (Non-explosion-proof)



Technical specifications:

Model: **HBLB19-3-15-110V**

Name: Electric Self-priming Diaphragm Pump

Flow range: 20 to 40 L/min

Nominal diameter: 3/4" BSPP Female (19 mm)

Motor: 370W (Non-explosion-proof)

Vertical suction distance: 2 to 3 meters



Technical specifications:

Model: **HBLB19-3-10-12V**

Name: Electric Self-priming Diaphragm Pump

Flow range: 20 to 30 L/min

Nominal diameter: 3/4" BSPP Female (19 mm)

Motor: 370W (Non-explosion-proof)

Vertical suction distance: 2 to 3 meters



Technical specifications:

Model: **HBLB19-3-10-24V**

Name: Electric Self-priming Diaphragm Pump

Flow range: 20 to 30 L/min

Nominal diameter: 3/4" BSPP Female (19 mm)

Motor: 370W (Non-explosion-proof)

Vertical suction distance: 2 to 3 meters

Horizontal head: 7 to 10 meters

Power supply: DC24V

Temperature Range:-20°C to+60°C