
Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

WGK24-19MT Gear Flow Meter



Accuracy:±1%
Medium:Most pure stable liquids
Body Material: PPS Plastic
Connection: 1/2" Male Thread BSPP
Thread Outer Diameter: 19 mm
Flow Rate:0.2 to 10 L/min.
Repeatability: ±0.5%
Max. Pressure:0.3 Mpa
Measurement: QTS, PTS, L, GAL, m³
Single Count Range:99999
Total Count Range:29999999
Weight:206 g

WGK24-12HT Gear Flow Meter



Accuracy:±1%
Medium:Most pure stable liquids
Body Material: PPS Plastic
Connection: 1/2" Hose Tail
Hose Tail Outer Diameter: 12 mm
Flow Rate:1 to 15 L/min.
Repeatability: ±0.5%
Max. Pressure:0.3 Mpa
Measurement: QTS, PTS, L, GAL, m³
Single Count Range:99999
Total Count Range:29999999
Weight:208 g

WGK24-33FT Gear Flow Meter



Accuracy:±1%
Medium:Most pure stable liquids
Body Material: Aluminum Alloy
Connection: 1" Female Thread BSPP
Thread Inner Diameter: 33 mm
Flow Rate:3 to 100 L/min.
Repeatability: ±0.5%
Max. Pressure:0.6 Mpa
Measurement: QTS, PTS, L, GAL, m³
Single Count Range:99999
Total Count Range:29999999
Weight:436 g

WGK24-33MT Gear Flow Meter



Accuracy:±1%
Medium:Most pure stable liquids
Body Material: PPS Plastic
Connection: 1" Male Thread BSPP
Thread Outer Diameter: 33 mm
Flow Rate:3 to 100 L/min.
Repeatability: ±0.5%
Max. Pressure:0.3 Mpa
Measurement: QTS, PTS, L, GAL, m³
Single Count Range:99999
Total Count Range:29999999
Weight:215 g