

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

DCEX56 Series of DC12V/DC24V Explosion-proof 15GPM Diesel Gasoline Transfer Pump Kits



This fuel transfer pump is designed for mounting on barrels or tanks, offering a safer and more efficient way to transfer diesel, gasoline, kerosene, mineral spirits, heptane, and hexane. Specifically designed for fueling gasoline. It features a durable iron pump head and a 100% copper wire motor for enhanced safety and performance.

Key Features:

- Explosion-proof protection
- Self-priming pump with built-in bypass valve
- Thermal overload protection
- Equipped with fuel filter and connectors
- 30-minute duty cycle (not intended for continuous operation)

Available Models:

- Maximum Flow Rate: 15 GPM (57 LPM) / 20 GPM (76 LPM) for option
- Motor Power: 1/4 HP (about 186 W)
- Voltage: DC12V or DC24V for option
- Threaded Tank Adapter: 2" NPT
- Nozzle Hanger: Included
- Color: Blue, Red, Yellow, Black etc. Customized on detailed requirement.



Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

DCEX56 Series of DC12V/DC24V Explosion-proof 15GPM Diesel Gasoline Single Transfer Pump



It is specifically designed for fueling gasoline. It features a durable iron pump head and a 100% copper wire motor for enhanced safety and performance. Ideal for transferring and dispensing gasoline, unleaded petrol, diesel, kerosene, Stoddard solvent, heptane, and mineral spirits. Suitable for use in fuel pumps, stationary fuel transfer systems, and other fixed installations. Perfect for caravans, boats, motorhomes, industrial and agricultural applications.

Specifications:

Explosion-proof sealed permanent magnet motor (specially designed for gasoline and petrol transfer)
Rainproof and waterproof pump body
Pump body material: Heavy-duty cast iron
Built-in strainer and automatic bypass valve
Thermal overload protection for safe operation
Compact and portable design — easy to install, operate, and maintain

Technical Details:

Power: 1/4Hp / about 186W
Voltage: 12V DC or 24V DC
Current Draw: 15A
Flow Rate: 57 - 75 L/min (depending on fluid type and head pressure)
Inlet/Outlet: 1" BSP thread (comes with hose adaptor and strainer)
Delivery Head: 5 - 10 meters
Single Pump Dimensions: 28 × 18 × 18 cm

Package Includes

- 1 × Fuel transfer pump
- 1 × Micro-mesh fuel filter
- 2 × Hose fittings
- 1 × User manual



Parameters:Explosion-Proof Type

Model: **DCEX56-12V/24V-K**
Name: DC Self-priming Gasoline Transfer Pump Kits
Flow Rate: 20 to 50L/min
Diameter Size: inlet DN25, Outlet DN25
Power: 1/4 Hp, (about 186 W of Power)
Vertical Distance: 2 to 4 meters
Voltage: DC12V/24V for option
Horizontal Distance: 5 to 10 meters
Temperature Range:-20°C to+60°C