

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

Explosion-Proof & Silent AC Self-Priming Oil Transfer Pump for Industrial Fuel Handling

This series of products is mainly used for refueling and transportation of mining machinery, generator sets and other fuel-consuming equipment, fishing boats, cruise ships and small refueling points. Cast iron pump body, anti-corrosion, coating, internal and external filters, easy to clean, aluminum alloy shell of electric motor. These pumps have the advantages of fast self-priming, high lift, small size, and easy portability.

They are light in weight, easy to move. The product can be equipped with various fuel nozzles(manual nozzle or automatic shut-off nozzle) and hose couplings or hose swivels according to customer's requirements to make it more convenient to use.

If the motor is marked with an EX explosion-proof sign, it indicates that this pump can be used for transporting gasoline; if the motor is not marked with an EX sign, it means that this pump cannot be used for petroleum products with low flash points such as gasoline.



Parameters:Explosion-Proof &Silent Type
Model: **HBJBZL-S-60EX-AC220**
Name: AC Self-priming Oil transfer Pump
Flow Rate:40 to 60L/min
Diameter Size: DN25
Motor Power: 550W
Vertical Distance: 2 to 4 meters
Voltage: AC220V 50 Hz
Horizontal Distance: 15 meters
Temperature Range:-20°C to+60°C



Parameters:Explosion-Proof Type
Model: **HBJBZL-60EX-AC220**
Name: AC Self-priming Oil Transfer Pump
Flow Rate:40 to 60L/min
Diameter Size: DN25
Motor Power: 550W
Vertical Distance: 2 to 4 meters
Voltage: AC220V 50 Hz
Horizontal Distance: 15 meters
Temperature Range:-20°C to+60°C



Parameters:Explosion-Proof Type
Model: **HBJBZL-80EX-AC220**
Name: AC Self-priming Oil Transfer Pump
Flow Rate: 60 to 80L/min
Diameter Size: DN25
Motor Power: 750W
Vertical Distance: 2 to 4 meters
Voltage: AC220V 50Hz
Temperature Range:-20°C to+60°C



Parameters:Explosion-Proof &Silent Type
Model: **HBJBZL-S-80EX-AC220**
Name: AC Self-priming Oil Transfer Pump
Flow Rate: 60 to 80L/min
Diameter Size: DN25
Motor Power: 750W
Vertical Distance: 2 to 4 meters
Voltage: AC220V 50Hz
Temperature Range:-20°C to+60°C