

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

## Explosion-Proof & Silent AC High-Flow Oil Transfer Pump for Industrial Fuel and Chemical Liquids

This series of products is mainly used for refueling and transportation of mining machinery, generator sets and other fuel-consuming equipment, fishing boats, cruise ships and small refueling points. Cast iron pump body, anti-corrosion, coating, internal and external filters, easy to clean, aluminum alloy shell of electric motor. These pumps have the advantages of fast self-priming, high lift, small size, and easy portability.

They are light in weight, easy to move. The product can be equipped with various fuel nozzles(manual nozzle or automatic shut-off nozzle) and hose couplings or hose swivels according to customer's requirements to make it more convenient to use.

If the motor is marked with an EX explosion-proof sign, it indicates that this pump can be used for transporting gasoline; if the motor is not marked with an EX sign, it means that this pump cannot be used for petroleum products with low flash points such as gasoline.



Parameters: Explosion-Proof Type  
Model: **HBJBZL-140EX-AC220**  
Name:AC Self-priming Oil Transfer Pump  
Flow Rate: 100 to 140L/min  
Diameter Size: DN40/1.5 inch  
Motor Power: 1100W  
Vertical Distance: 2 to 4 meters  
Horizontal Distance: 15 meters  
Voltage: AC220V 50Hz  
Temperature Range:-20°C to+60°C



Parameters: Explosion-proof Type  
Model: **HBJBZL-350EX-AC220**  
Name:AC Self-priming Oil Transfer Pump  
Flow Rate:275 to 350L/min  
Diameter Size: DN50/2 inch  
Motor Power: 2200W  
Vertical Distance: 2 to 4 meters  
Horizontal Distance: 15 meters  
Voltage: AC220V 50Hz  
Temperature Range:-20°C to+60°C



Parameters: Explosion-Proof Type  
Model: **HBJYBJB-100EX-AC220**  
Name:AC Self-priming Oil Transfer Pump  
Flow Rate:70 to 100L/min  
Diameter Size: DN25  
Motor Power: 750W  
Vertical Distance: 2 to 4 meters  
Voltage: AC220V 50 Hz  
Horizontal Distance: 25 meters  
Temperature Range:-20°C to+60°C



**Parameters:**Explosion-Proof &Silent Type  
Model: **HBJBZL-S-330EX-AC220**  
Name: AC Centrifugal Oil Transfer Pump  
Flow Rate: 230 to 330L/min  
Diameter Size: DN50  
Motor Power: 2200W  
Voltage: AC220V 50 Hz  
Horizontal Distance: 15Meter  
Sizes: 580 X420X500 mm  
Temperature Range:-20°C to+60°C