

Add:Bali Village Qiaoxia Town, Yongjia County, Wenzhou City, Zhejiang Province, China.

Explosion-Proof & Silent AC High-Capacity Oil Transfer Pump for Industrial Fuel and Bulk Liquid Handling

This series of products is mainly used for refueling and transportation of mining machinery, generator sets and other fuel-consuming equipment, fishing boats, cruise ships and small refueling points. Cast iron pump body, anti-corrosion, coating, internal and external filters, easy to clean, aluminum alloy shell of electric motor. These pumps have the advantages of fast self-priming, high lift, small size, and easy portability.

They are light in weight, easy to move. The product can be equipped with various fuel nozzles(manual nozzle or automatic shut-off nozzle) and hose couplings or hose swivels according to customer's requirements to make it more convenient to use.

If the motor is marked with an EX explosion-proof sign, it indicates that this pump can be used for transporting gasoline; if the motor is not marked with an EX sign, it means that this pump cannot be used for petroleum products with low flash points such as gasoline.



Parameters:Explosion-Proof &Silent Type
Model: **HBJBZL-S-660EX-AC220**
Name: AC Centrifugal Oil Transfer Pump
Flow Rate: 460 to 660L/min
Diameter Size: DN80
Motor Power: 3000W
Voltage: AC220V 50 Hz
Horizontal Distance: 15 meters
Sizes: 580 X420X500 mm



Parameters:Explosion-Proof &Silent Type
Model: **HBJBZL-S-400EX-AC220**
Name: AC Centrifugal Oil Transfer Pump
Flow Rate: 400L/min
Diameter Size: DN50
Motor Power: 1100W
Voltage: AC220V 50 Hz
Horizontal Distance: 15 meters
Temperature Range:-20°C to+60°C



Parameters: Explosion-Proof Type
Model: **HBJBZL-R-140EX-AC220**
Name:AC Self-priming Oil Transfer Pump
Flow Rate: 140L/min
Diameter: DN40
Motor Power: 1100W
Vertical Distance: 2 to 4 meters
Voltage: AC220V 50 Hz
Horizontal Distance: 15 meters
Temperature Range:-20°C to+60°C



Parameters: Explosion-Proof Type
Model: **YB80-750EX-AC380**
Name:AC Self-priming Oil Transfer Pump
Flow Rate: 750L/min
Diameter Size: DN80
Motor Power: 4000W
Vertical Distance: 3 to 5 meters
Voltage: AC380V 50 Hz
Horizontal Distance: 15 meters
Temperature Range:-20°C to+60°C