

HRD34XXEX and HRD11XXEX Series High-Performance Electric Retraction Fuel Rubber Hose Reel

This Series of Electric Retraction Fuel Delivery Hose Reels are equipped with Viton seals, incorporate metal forms and a heavy-duty base to ensure the greatest possible strength and are ideal for mobile and permanent-mount applications. These rugged, corrosion-resistant(stainless steel inlet and outlet pipe connectors are for option) reels are suitable for a wide variety of fuel applications including E85.They are supplied with our Viton O-ring style swivel. NOTE: Not recommended for jet fuel.



Features:

Voltage: DC12V/DC24V
/AC220V/AC380V for Option

Ideal for mobile and permanent mount applications

Suitable for a wide variety of fuel applications including E85 (not recommended for jet fuel)

Incorporates metal forms to ensure the greatest possible strength

This series of reels can usually wind 3/4 inch diameter fuel delivery hose from 10 to 30 meters. If the size of the inlet and outlet connector is changed to 1 inch, it can wind 1 inch diameter fuel delivery hose from 10 to 25 meters. We can produce the above electric retraction hose reel with hoses at different sizes and different lengths according to user's detailed requirements.

Specifications: Max. Working temperature:65°C

Item No.	Hose	Hose I.D.	Hose O.D.	Hose Length	Max. Pressure	Reel Inlet	Reel Outlet
HRD3410E	without				0.3 Mpa	3/4"	3/4"
HRD3415E	without				0.3 Mpa	3/4"	3/4"
HRD3420E	without				0.3 Mpa	3/4"	3/4"
HRD3425E	without				0.3 Mpa	3/4"	3/4"
HRD3430E	without				0.3 Mpa	3/4"	3/4"
HRD3410EJ	with	19 mm	30 mm	10 Meters	0.3 Mpa	3/4"	3/4"
HRD3415EJ	with	19 mm	30 mm	15 Meters	0.3 Mpa	3/4"	3/4"
HRD3420EJ	with	19 mm	30 mm	20 Meters	0.3 Mpa	3/4"	3/4"
HRD3425EJ	with	19 mm	30 mm	25 Meters	0.3 Mpa	3/4"	3/4"
HRD3430EJ	with	19 mm	30 mm	30 Meters	0.3 Mpa	3/4"	3/4"
HRD1110E	without				0.3 Mpa	1"	1"
HRD1115E	without				0.3 Mpa	1"	1"
HRD1120E	without				0.3 Mpa	1"	1"
HRD1125E	without				0.3 Mpa	1"	1"
HRD1110EJ	with	25 mm	37 mm	10 Meters	0.3 Mpa	1"	1"
HRD1115EJ	with	25 mm	37 mm	15 Meters	0.3 Mpa	1"	1"
HRD1120EJ	with	25 mm	37 mm	20 Meters	0.3 Mpa	1"	1"
HRD1125EJ	with	25 mm	37 mm	25 Meters	0.3 Mpa	1"	1"

Note: The ADBLUE urea reel and E85 ethanol gasoline reel are optional. At the same time, it is necessary to replace the inlet and outlet connectors of the reel rack and all pipes in contact with the liquid medium with stainless steel material, and replace the sealing materials with seals resistant to ADBLUE urea reel and E85 alcohol gasoline.

Very Important: They are for fueling diesel, Kerosene, not for gasoline.The Electric Retraction Fuel Delivery Hose Reels for gasoline or other low-ignition point medium must be with explosion-proof type Electric Mechanism.

HB Equipment shall be used in compliance with applicable country, province and local laws and regulations. Products selection shall be based on physical specifications and limitations and compatibility with the environment.