

## HRO/GXXXXA Series High-Pressure Automatic Oil & Grease Rubber Hose Reel - Industrial & Automotive Applications

HROXXXXA Series of Automatic Oil Hose Reels are projected to work up to 150 BAR pressure, it can be used in all industries,workshops,service stations, garages, etc.



**Features:** The 4 reel ball bearings on the arms facilitate the unrolling of the hose,avoiding friction that would cause a gradual deterioration. The hose can be locked at the desired length. Ratchet prevents unlock when hose is completely extended. Corrosion resistant: the hot galvanized steel structure is moulded and coated with electrostatic polyester powder UV rays resistant. Easy and versatile installation through the rotating support plate and the adjustable arm positions. Spring-driven retractable hose. Hose stop, reduce pressure losse. Compatibility: Bolts and nuts are made of stainless steel.



Spring driven double arm hose reel.  
 Designed to transfer engine oil.  
 Heavy duty construction for long life industrial and automotive applications.  
 High quality impact resistant steel drum.  
 Maximum working pressure: 150bar.  
 All fittings (fluid pass)in CuZn40Pb2(brass).  
 Wall, ceiling or floor mounted.  
 NPT1/2", 1/4" 3/8" inlet/outlet

### Specifications:

Item No.	Hose	Medium	Hose Length	Max. Pressure	Reel Inlet	Reel outlet
HRO1215	without	Oil, Lub		150 bar	NPT1/2" M	NPT1/2" M
HRO1215A	with	Oil, Lub	15 Meters	150 bar	NPT1/2" M	NPT1/2" M
HRO1210A	with	Oil, Lub	10 Meters	150 bar	NPT1/2" M	NPT1/2" M

HRGXXXXA Series of Automatic Grease Hose Reels are projected to work up to 400 BAR pressure, it can be used in all industries,workshops,service stations, garages, etc.

### Specifications:

Item No.	Hose	Medium	Hose Length	Max. Pressure	Reel Inlet	Reel outlet
HRG1415	without	Grease, Water		400 bar	NPT1/4" M	NPT1/4" M
HRG1415A	with	Grease, Water	15 Meters	400 bar	NPT1/4" M	NPT1/4" M
HRG3815	without	Grease, Water		400 bar	NPT3/8" M	NPT3/8" M
HRG3815A	with	Grease, Water	15 Meters	400 bar	NPT3/8" M	NPT3/8" M